



(248) 545-4441
info@jetsetspray.com
http://jetsetspray.com

JET-SET® MOD-1

SINGLE PUMP MANIFOLD W/AIR SWITCH



The MOD-1 JET-SET® spray system comes standard with our 5 Gallon stainless steel tank with sight gauge, reusable filter, and air regulator. This system includes one JET-SET 9100 stainless steel piston pump (0-5cc per stroke) with 5 outlets for spray nozzles. The 9100 pump is engaged using a Pneumatic actuator switch for system activation.

The Pneumatic actuator switch can be placed so the mechanical movement of the machine in use will trigger the system.


The MOD-1 comes standard with a 9100 pump that will give you millions of cycles of maintenance free operation. All JET-SET® pumps provide easy volume regulation by turning the nuraled regulator knob found on top of the 9100 pump. The 9100 pump can be regulated from 0 to 5 cc per cycle.



Established 1963
jetsetspray.com

JET-SET® MOD-1

SINGLE PUMP MANIFOLD W/AIR SWITCH



- | | |
|---|--|
| 1) 9100: Large S.S. Pump
Exchange w/ 5 Outlets | 6) 815: Cable Clamp |
| 2) 810: Draw Latch | 7) 816-SA: Air Switch w/
Triple Tube Assembly |
| 3) 620: Standard Filter | 8) 505-A: Stopcock |
| 4) 525: 5-1/2 Sight Glass w/ Fitting | 9) 724-L: 1/2" NPT Ball Valve |
| 5) 1501: SMC Style Filter / Regulator Unit | 10) 725: 1/2 " NPT Tube Stem |



JET-SET® MOD-1

SINGLE PUMP MANIFOLD W/AIR SWITCH



The MOD-1 JET-SET® spray system comes standard with our 5 Gallon stainless steel tank with sight gauge, reusable filter, and air regulator. This system includes one JET-SET 9100 stainless steel piston pump (0-5cc per stroke) with 5 outlets for spray nozzles. The 9100 pump is engaged using a Pneumatic actuator switch for system activation.


The Pneumatic actuator switch can be placed so the mechanical movement of the machine in use will trigger the system.

The MOD-1 comes standard with a 9100 pump that will give you millions of cycles of maintenance free operation. All JET-SET® pumps provide easy volume regulation by turning the nuraled regulator knob found on top of the 9100 pump. The 9100 pump can be regulated from 0 to 5 cc per cycle.



JET-SET® MOD-1

SINGLE PUMP MANIFOLD W/AIR SWITCH



- 1) 9100: Large S.S. Pump Exchange w/ 5 Outlets
- 2) 810: Draw Latch
- 3) 620: Standard Filter
- 4) 525: 5-1/2 Sight Glass w/ Fitting
- 5) 1501: SMC Style Filter / Regulator Unit

- 6) 815: Cable Clamp
- 7) 816-SA: Air Switch w/ Triple Tube Assembly
- 8) 505-A: Stopcock
- 9) 724-L: 1/2" NPT Ball Valve
- 10) 725: 1/2" NPT Tube Stem





INSTALLATION

1. Using the template provided, select a location that will be convenient for filling the tank and making setup changes.
2. Drill and tap two holes for bolts to support the module. The template will provide you with the exact location of the holes.
3. Now hang the module and connect shop air to the ¼" F.P.T. brass fitting located on the left side of the module.
- 4a. Place the air switch where the trigger rod* can best be activated by mechanical movement. The switch may be adjusted to fire in either direction or in both directions. To change direction: See attached "714N Air Switch Installation Data."
- 4b. *If installing an electrically activated module, a four way solenoid has been provided to activate the pump. Simply complete the circuit from the four way solenoid to the switch of your choice. See attached "1400N Solenoid Valve Instructions" or "1400 SMC Valve Instructions"
5. Keeping all the nozzle leads the same approximate length, plug the quick disconnect hose connectors into the bottom of the Module. Keeping the nozzle leads the same length assures even distribution of fluid to each nozzle. Position nozzles where needed.
6. Fill the tank with lubricant and turn the slot in the teecock shutoff, located at the top right of the control panel, to a vertical position. When using the standard high pressure nylon tubing provided, we recommend spraying light viscosity fluids. A copper tubing conversion kit is available for spraying heavy viscosity fluids.
7. With the large knurled knob on the control panel turned all the way out, hand activate the air switch until all air is out of the system. See attached "How to Bleed Air From The Manifold of #9100 Pump"





JET-SET® GUIDES

Module Mounting Instructions

(248) 545-4441
info@jetsetspray.com
<http://jetsetspray.com>

FINAL ADJUSTMENT

1. To adjust the volume of liquid being sprayed, turn the large knurled knob on the control panel clockwise to decrease, and counterclockwise to increase. With the air regulator set at high pressures it may be necessary to hand activate the air switch to relieve air pressure and allow the knob to move freely.
2. To adjust the air pressure on the unit, turn the adjustment knob which is under the panel and just below the gauge. This adjustment will regulate the velocity of the spray. The higher the air pressure, the higher the velocity of spray. We suggest lowering the air pressure until the best spray pattern has been obtained.
3. Position the spray nozzles for the coverage desired. The distance away from the surface will determine the area of coverage. If longer nozzle leads are required or nozzle placement is a question CALL YOUR JETSET® DISTRIBUTOR or visit us online at <http://www.JetSetSpray.com> . JETSET® distributors carry a complete line of interchangeable spray tips for changing spray patterns, nozzle holders and the required high pressure nylon tubing.



Established 1963
jetsetspray.com



JET-SET® GUIDES

Spray System Troubleshooting

(248) 545-4441
 info@jetsetspray.com
 http://jetsetspray.com

System Troubleshooting

Problem	Possible Cause	Possible Solution
Entire system will not operate	1. Solenoid Wiring	1. Check for correct wire hookup
		1A. Check for proper placement of sensor or micro switch
	2. Loss of Air Pressure	2. Check air regulator for adequate pressure adjust for operation at 10PSI-130PSI.

Pump Troubleshooting

Problem	Possible Cause	Possible Solution
Pump Will Not Operate	1. Pump will not draw fluid in feedline.	1. Check tank fluid level, be sure the fluid stopcock is in open position.
		1a. Be sure the filter surface is clean.
	2. Pump may have an air lock in the fluid discharge area.	2. Follow pump priming procedure. Refer to "Pump Priming Instruction Sheet".
		3. Oil in the feedline rises and falls with each cycle of operation.
	4. Fluid in the spray line rises and falls with each cycle of operation.	4. Inspect Outlet SS Seat for proper placement of spring and SS Ball. Inspect for foreign matter lodged between seat and ball that may prevent proper seating action.
	5. Pump passes air into the nozzle line while in idle position or during operation.	5. Check pump position "O" rings for wear. Replace seals if needed.
		5a. Be sure fluid connectors supplying the pump are tight.



Established 1963
 jetsetspray.com



JET-SET® GUIDES

Spray System Troubleshooting

(248) 545-4441
info@jetsetspray.com
http://jetsetspray.com

Spray Troubleshooting

Problem	Possible Cause	Possible Solution
Poor Spray Pattern	1. Low air regulator pressure.	1. Increase regulator pressure to obtain optimum pattern.
	2. Contaminated nozzle ballcheck and strainer.	2. Clean or replace as necessary. Make sure all nozzles have ballcheck for proper spray checking action.
	3. Flex spray lines too long.	3. Keep to a minimum all nozzle leads. When using a lubricant with higher viscosity, replace nylon leads with rigid tubing for best spraying results.
	4. Air is trapped in spray lines or in a pump outlet manifold.	4. Bleed all nozzle leads of air. Refer to "Pump Priming Instruction Sheet" to clear air in pump.

TO ASSURE CONTINUED TROUBLE FREE OPERATION OF YOUR JETSET® SYSTEM, A DAILY CHECK OF THE FOLLOWING IS RECOMMENDED.

1. Drain air filter regulator bowl of moisture buildup.
2. Check spray nozzles for proper placement and spray quality.
3. Check for contaminants in holding tank. Clean filter element as needed.
4. Check for proper lubricant level and refill as needed to assure continual operation.



Established 1963
jetsetspray.com




JET-SET® GUIDES

9100 Pump

(248) 545-4441
info@jetsetspray.com
http://jetsetspray.com

JET-SET® #9100 Pump

STAINLESS STEEL PUMP



Individual part numbers:

- | | |
|---|--|
| 1) 9114-A: End Cap Assembly | 10) 9102*: Stainless Steel Check Ball |
| 2) 9121: Socket Cap Screw | 11) 9103: Stainless Steel Check Spring |
| 3) 9112*: Viton O-Ring | 12) 811: Brass Elbow |
| 4) 9111: Stainless Steel Piston | 13) 802: Midget Socket |
| 5) 9108*: Viton O-Ring | 14) 802-V: Valve Core |
| 6) 9113*: Gasket | 15) 9104-0: Outlet Ball Check |
| 7) 9101: Stainless Steel Pump Body | 16) 9118*: Viton O-Ring |
| 8) 897: Elbow Connector | 17) *Seal Kit available : All parts with** are |
| 9) 9104-I: Stainless Steel Inlet Ball Check | included in a replacement 9100 Seal Kit |



Established 1963
jetsetspray.com



JET-SET® GUIDES

9100 Pump

(248) 545-4441
info@jetsetspray.com
<http://jetsetspray.com>

JET-SET® #9100 Pump

STAINLESS STEEL PUMP



All JET-SET® Module Systems have the new stainless steel JET-SET® pump designed for long life cycles. Utilizing stainless components and viton seal. The #9100 pump will give millions of cycles of maintenance-free operation. All JET-SET® pumps provide easy volume regulation by turning the large knob on top of the pump. You can regulate the output of fluid from 0 to 5 cc per cycle. One to three pumps may be mounted in the system. All pumps have five quick disconnect fittings for nozzles.



Established 1963
jetsetspray.com




JET-SET® GUIDES

How to Bleed 9100 Pump

(248) 545-4441
info@jetsetspray.com
http://jetsetspray.com

***** PLEASE NOTE: Adjustment knob should be in the full open position (More >) ***
before each and every time the pump is to be primed.**



A #9100 JETSET® pump comes from our factory fully primed, tested and ready to use. It has been found, however, that when first installing the JETSET® system, small amounts of air might be trapped in the manifold of the #9100 pump. This is not noticeable when spraying at full volume, only when spraying very small amounts. Then, the pump may need to be reprimed. For best results, bleed all five connections, in the order shown. Simply plug a nozzle into each connection while the pump is being activated. Release just enough fluid to eliminate air. This will ensure a good spray pattern and eliminate drippage.

This procedure should never have to be repeated, unless the system runs dry and loses its prime.



Established 1963
jetsetspray.com




JET-SET® GUIDES

Tips For Spraying

(248) 545-4441
 info@jetsetspray.com
 http://jetsetspray.com

The JETSET® Hydraulic Spray System Assures a controlled deposit on any configuration. First, the spray displacement can vary from zero to full capacity by adjusting the volume control on the pump. And second, the velocity can be controlled from a soft, gentle spray to a full strong blast by regulating the pressure in the air supply.


The Following three sketches show how the coverage and pattern can be varied without changing tips.



1 DISTANCE FROM TIP INCREASES COVERAGE



2 ANGLE OF TIP BROADENS COVERAGE



3 WIDTH OF FLAT SPRAY COVERAGE CAN BE CHANGED BY TURNING TIP

JET-SET® HYDRAULIC SPRAY KITS ARE SHIPPED WITH AN 80015 FLAT SPRAY TIP. THE FOLLOWING INTERCHANGEABLE TIPS ARE AVAILABLE FOR SPECIFIC NEEDS.



SOLID ROUND SPRAY

CODE	ACTUAL ORIFICE	ANGLE
TG 0.4	.022	63°
TG 1	.036	60°
TG 2	.047	50°
TG 3	.062	65°

*

* Popular Sizes




HOLLOW ROUND SPRAY

CODE	ACTUAL ORIFICE	ANGLE
TY 14	.059	68°
TX 10	.060	76°
T8W	.063	136°

*

* Popular Sizes




FLAT SPRAY

CODE	EQUIVALENT ORIFICE	ANGLE
5001	.026	60°
80015	.031	90°
110015	.031	120°

**

*

* Popular Sizes ** Most Popular



"OFF-SIDE" DEFLECTOR FLAT SPRAY

CODE	ACTUAL ORIFICE	ANGLE
TK 1.5	.040	140°
TK 2.5	.051	140°

*

* Popular Sizes

NOTE: Other tips are available. For recommendation, submit pint sample of liquid and details of operation.




Established 1963
 jetsetspray.com



JET-SET® GUIDES

Spray Angle and Coverage

(248) 545-4441
 info@jetsetspray.com
 http://jetsetspray.com



Tabulated spray angles indicate approximate spray coverages based on spray or distribution of water. In actual spraying, the effective spray angle varies with spray distance. Liquids more viscous than water form relatively smaller spray angles (or even solid stream), depending upon viscosity, nozzle capacity and spraying pressure. Liquids with surface tensions lower than water will produce relatively wider spray angles than those listed for water. This table list the theoretical coverage of spray patterns as calculated from the included spray angle of the spray and the distance from the nozzle orifice. Values are based on the assumption that the spray angle remains the same throughout the entire spray distance. In actual practice the tabulated spray angle does not hold for long spray distances. If spray coverage requirement is critical contact JETSET® for help in determining the specs.

Theoretical Spray Coverage
 at Various Distances in Inches (cm) from Nozzle Orifice

Spray Angle	2"	5 cm	4"	10 cm	6"	15 cm	8"	20 cm	10"	25 cm	12"	30 cm	15"	40 cm	18"	50 cm	24"	60 cm	30"	70 cm	36"	80 cm	48"	100 cm
5°	.2	.4	.4	.9	.5	1.3	.7	1.8	.9	2.2	1.1	2.6	1.3	3.5	1.6	4.4	2.1	5.2	2.6	6.1	3.1	7.0	4.2	8.7
10°	.4	.9	.7	1.8	1.1	2.6	1.4	3.5	1.8	4.4	2.1	5.3	2.6	7.0	3.1	8.8	4.2	10.5	5.2	12.3	6.3	14.0	8.4	17.5
15°	.5	1.3	1.1	2.6	1.6	4.0	2.1	5.3	2.6	6.6	3.2	7.9	3.9	10.5	4.7	13.2	6.3	15.8	7.9	18.4	9.5	21.1	12.6	26.3
20°	.7	1.8	1.4	3.5	2.1	5.3	2.8	7.1	3.5	8.8	4.2	10.6	5.3	14.1	6.4	17.6	8.5	21.2	10.6	24.7	12.7	28.2	16.9	35.3
25°	.9	2.2	1.8	4.4	2.7	6.7	3.5	8.9	4.4	11.1	5.3	13.3	6.6	17.7	8.0	22.2	10.6	26.6	13.3	31.0	15.9	35.5	21.2	44.3
30°	1.1	2.7	2.1	5.4	3.2	8.0	4.3	10.7	5.4	13.4	6.4	16.1	8.1	21.4	9.7	26.8	12.8	32.2	16.1	37.5	19.3	42.9	25.7	53.6
35°	1.3	3.2	2.5	6.3	3.8	9.5	5.0	12.6	6.3	15.8	7.6	18.9	9.5	25.2	11.3	31.5	15.5	37.8	18.9	44.1	22.7	50.5	30.3	63.1
40°	1.5	3.6	2.9	7.3	4.4	10.9	5.8	14.6	7.3	18.2	8.7	21.8	10.9	29.1	13.1	36.4	17.5	43.7	21.8	51.0	26.2	58.2	34.9	72.8
45°	1.7	4.1	3.3	8.3	5.0	12.4	6.6	16.6	8.3	20.7	9.9	24.9	12.4	33.1	14.9	41.4	19.9	49.7	24.8	58.0	29.8	66.3	39.7	82.8
50°	1.9	4.7	3.7	9.3	5.6	14.0	7.5	18.7	9.3	23.3	11.2	28.0	14.0	37.3	16.8	46.6	22.4	56.0	28.0	65.3	33.6	74.6	44.8	93.3
55°	2.1	5.2	4.2	10.4	6.3	15.6	8.3	20.8	10.3	26.0	12.5	31.2	15.6	41.7	18.7	52.1	25.0	62.5	31.2	72.9	37.5	83.3	50.0	104
60°	2.3	5.8	4.6	11.6	6.9	17.3	9.2	23.1	11.5	28.9	13.8	34.6	17.3	46.2	20.6	57.7	27.7	69.3	34.6	80.8	41.6	92.4	55.4	115
65°	2.5	6.4	5.1	12.7	7.6	19.1	10.2	25.5	12.7	31.9	15.3	38.2	19.2	51.0	22.9	63.7	30.5	76.5	38.2	89.2	45.8	102	61.2	127
70°	2.8	7.0	5.6	14.0	8.4	21.0	11.2	28.0	14.0	35.0	16.8	42.0	21.0	56.0	25.2	70.0	33.6	84.0	42.0	98.0	50.4	112	67.2	140
75°	3.1	7.7	6.1	15.4	9.2	23.0	12.3	30.7	15.3	38.4	18.4	46.0	23.0	61.4	27.6	76.7	36.8	92.1	46.0	107	55.2	123	73.6	153
80°	3.4	8.4	6.7	16.8	10.1	25.2	13.4	33.6	16.8	42.0	20.2	50.4	25.2	67.1	30.3	83.9	40.3	101	50.4	118	60.4	134	80.6	168
85°	3.7	9.2	7.3	18.3	11.0	27.5	14.7	36.7	18.3	45.8	22.0	55.0	27.5	73.3	33.0	91.6	44.0	110	55.0	128	66.0	147	88.0	183
90°	4.0	10.0	8.0	20.0	12.0	30.0	16.0	40.0	20.0	50.0	24.0	60.0	30.0	80.0	36.0	100	48.0	120	60.0	140	72.0	160	96.0	200
95°	4.4	10.9	8.7	21.8	13.1	32.7	17.5	43.7	21.8	54.6	26.2	65.5	32.8	87.3	39.3	109	52.4	131	65.5	153	78.6	175	105	218
100°	4.8	11.9	9.5	23.8	14.3	35.8	19.1	47.7	23.8	59.6	28.6	71.5	35.8	95.3	43.0	119	57.2	143	71.6	167	85.9	191	114	238
110°	5.7	14.3	11.4	28.6	17.1	42.9	22.8	57.1	28.5	71.4	34.3	85.7	42.8	114	51.4	143	68.5	171	85.6	200	103	229	-	286
120°	6.9	17.3	13.9	34.6	20.8	52.0	27.7	69.3	34.6	86.6	41.6	104	52.0	139	62.4	173	83.2	208	104	243	-	-	-	-
130°	8.6	21.5	17.2	42.9	25.7	64.3	34.3	85.8	42.9	107	51.5	129	64.4	172	77.3	215	103	257	-	-	-	-	-	-
140°	10.9	27.5	21.9	55.0	32.9	82.4	43.8	110	54.8	137	65.7	165	82.2	220	98.6	275	-	-	-	-	-	-	-	-
150°	14.9	37.3	29.8	74.6	44.7	112	59.6	149	74.5	187	89.5	224	112	299	-	-	-	-	-	-	-	-	-	-
160°	22.7	56.7	45.4	113	68.0	170	90.6	227	113	284	-	-	-	-	-	-	-	-	-	-	-	-	-	-
170°	45.8	114	91.6	229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-



Established 1963
 jetsetspray.com



JET-SET® GUIDES

#714-N Air Switch

Installation Data


(248) 545-4441
 info@jetsetspray.com
 http://jetsetspray.com

This chart is FULL SCALE layout of the movement required to actuate a 714-N through the various segments of its travel, superimposed on a grid of 1/4 " squares.

The small circles represent the 3/4 " diameter rollers or the standard operating levers. The inner group of circles is the path followed by the roller of all short lever operators (1 1/2 " radius). The outer group of the circle is the path followed by long lever operators (3" radius).





Thus, you can count squares (or scale it off) and find the vertical and horizontal travel your Cam must provide to actuate the valve properly.

If your lever radius or roller diameter are non-standard, you can draw your lever on a piece of tracing paper, stick a pin through its center and the pivot point of the chart, and rotate the tracing paper around the pin. Thus you can see the path your lever must follow, and the linear travel needed.



FULL SIZE CHART - 1/4" SQUARE GRID

JET-SET LIMIT VALVE OPERATING HEADS CAN BE ROTATED TO FOUR POSITIONS AND THE DIRECTION OF OPERATION CHANGED FROM UNIVERSAL TO "CW" ONLY OR "CCW" ONLY AS SHOWN BELOW



Established 1963
 jetsetspray.com




JET-SET® GUIDES

#714-N Air Switch

Installation Data

(248) 545-4441
 info@jetsetspray.com
 http://jetsetspray.com



ITEM NO.	NO. REQD.	DESCRIPTION	PART NO.
1	1	Seal	714-1
2	1	Spring	714-2
3	1	Operator Assembly	714-3
4	1	- Yoke	714-4
5	1	- Push Pin	714-5
6	1	- Pin	714-6
7	1	- Spring	714-7
8	1	- Plunger	714-8
9	1	- Operator Head Assembly	714-9
10	1	- Seal	714-10, 17, 21
11	1	- Shaft	714-11
12	4	Screw Assembly	714-12
13	1	Valve Body Assembly	
14	1	- Body	714-14
15	1	- Sleeve Ass'y with Seals	714-15
16	1	- - Sleeve Ass'y	714-16
17	4	- - Seal	714-10, 17, 21

ITEM NO.	NO. REQD.	DESCRIPTION	PART NO.
18	1	- Spring	714-18
19	1	- Stop Pin	714-19
20	1	- Spring Retainer	714-20
21	1	- Seal	714-10, 17, 21
22	1	- Screw	714-22
23	2	Screw	714-23
24	1	Name Plate	714-NP
26	1	Filter	714-26
28	1	Conduit Adapter Assembly	
29	3	Pipe Plug	714-29
30	1	Base	714-30
31	1	Gasket	714-31
32	4	Screw Assembly	714-32
33	1	Mounting Plate	731
34	2	Screws	733
35	1	Trigger Rod Assembly	717-N



Established 1963
 jetsetspray.com



JET-SET® GUIDES

Spray Tips

(248) 545-4441
info@jetsetspray.com
http://jetsetspray.com

Spray tips are available in a wide variety of materials, capacities, and patterns. For specific information about spray tips of or different patterns other than indicated here, please contact us.

The following spray tips are regularly stocked at **JET-SET®**

FLAT SPAY (TP)

Tip #	Orifice	Spray Angle (approx.)	TP
902- 5001	.026"	50° @ 40psi / 60° @ 80psi	
902- 6501	.026"	65° @ 40psi / 74° @ 80psi	
902- 80015	.031"	80° @ 40psi / 90° @ 80psi	
902- 800050	.018"	80° @ 20psi / 95° @ 80psi	
902- 110015	.031"	110° @ 40psi / 120° @ 80psi	

FULL CONE (TG)

Tip #	Orifice	Spray Angle (approx.)	TG
902- TG 0.3	.020"	50° @ 20psi / 61° @ 80psi	
902- TG 0.4	.022"	56° @ 20psi / 63° @ 80psi	
902- TG 0.6	.027"	54° @ 20psi / 62° @ 80psi	
902- TG 1	.036"	58° @ 20psi / 53° @ 80psi	
902- TG 2	.047"	50° @ 20psi / 46° @ 80psi	
902- TG 3	.062"	65° @ 20psi / 59° @ 80psi	



Established 1963
jetsetspray.com



JET-SET® GUIDES

Spray Tips

(248) 545-4441
info@jetsetspray.com
http://jetsetspray.com

DEFLECTED FLAT SPRAY (TK)

Tip #	Orifice	Spray Angle (approx.)	TK
902- TK 1.5	.040"	108° @ 20psi / 130° @ 60psi	
902- TG 2.5	.052"	122° @ 20psi / 133° @ 60psi	

HOLLOW CONE (TX/TY)

Tip #	Orifice	Spray Angle (approx.)	TX / TY
902- TX 10	.059"	68° @ 20psi / 74° @ 40psi	
902- TY 14	.070	70° @ 20psi / 76° @ 40psi	



Established 1963
jetsetspray.com



JET-SET® GUIDES

Nozzle Assemblies

(248) 545-4441
 info@jetsetspray.com
 http://jetsetspray.com

Part# 900 (O/A Length 1 7/8" Approx.)		Female Nozzle Assembly
1pc	901 Nozzle Nut	
1pc	902-80015 Standard Spray Tip	
1pc	903 20 (40) 20 or 40lb Check Valve	
2pc	904 Nozzle Bracket	
1pc	905 Nozzle Body	

Part# 900-1/8MT (O/A Length 1 3/4" Approx.)		Male Nozzle Assembly
1pc	901 Nozzle Nut	
1pc	902-80015 Standard Spray Tip	
1pc	903 20 (40) 20 or 40lb Check Valve	
2pc	904 Nozzle Bracket	
1pc	905-1/8 MT Nozzle Body	

Part# 902-80015-M20 (O/A Length 7/8" Approx)20lb Check Valve		Mini Nozzle
OR		
Part# 902-80015-MNV (O/A Length 7/8" Approx)No Check Valve		

Part# 908-SW 1/8x1/8 (O/A Length 1 1/4" Approx.)		Mini Nozzle
Swivel For 900-1/8M or 902-80015-M's		



Established 1963
 jetsetspray.com